

Power Units

GTR20 • HP08



GTR20



HP08

Hydraulic power to operate Stanley's line of hydraulic railroad tools is available in small, compact and efficient units like the HP08 and our new GTR20 which is about the size of a wheelbarrow.

Compact design is ideal for all your on-site hydraulic power needs. The ultra efficient hydraulic tool circuit cooling provides comfortable tool operation even in the most demanding environments.

Features

GTR20

- Compact and lightweight.
- 12 volt accessory outlet.
- Computerized electronic throttle control.
- In-tank hydraulic filtration.
- Pressurized engine oil lubrication.
- Locking handle.
- Electric Start.

HP08

- Comfortable self-locking handle.
- Low engine oil shut-off.
- Recoil start.
- Rugged steel wrap-around frame.

Specifications

	GTR20	HP08
Weight	330 lbs (150 kg)	133 lbs (60 kg)
Length	35 in. (90 cm)	28 in. (71 cm)
Width	23 in. (59 cm)	18.5 in. (47 cm)
Height	29 in. (74 mm)	21 in. (53 cm)
Pressure	2000 psi (140 bar)	2000 psi (140 bar)



Order Information

GTR20B02, 1, 10 gpm/40 lpm or 2, 5 gpm/20 lpm 18 hp Briggs & Stratton

GTR20H02, 1, 10 gpm/40 lpm or 2, 5 gpm/20 lpm 20 hp Honda

HP081523D, 5 gpm/20 lpm 9 hp Honda

Included Equipment

Auto Throttle, Wheels and Handles, Dual Circuit

Auto Throttle, Wheels and Handles, Dual Circuit



Power Units

MHP1

Features

- Integrated hydraulic tool circuit.
- Self propelled rubber tracks.
- Turns 360° within its own length.
- Carries over 1,000 lbs/454 kg.
- Climbs 60% grade.
- Large lifting eye for easy loading/unloading.
- Integral brake holds unit on incline upon release of controls.
- Self adjusting track tensioner.
- Self cleaning ballast and gravel from track mechanism.
- Removable side panels for flat-bed use.

The TracHorse is an all-terrain, self-propelled mobile hydraulic power pack that allows transportation of tools and equipment in most job site environments. Simple operating controls allow for maneuvering in a wide range of applications. The auxiliary hydraulic tool circuit is designed for continuous-duty applications and features the standard high-efficiency cooling found on all Stanley hydraulic power units.



Specifications

Load Capacity	1000 lbs (454 kg)
Tool Capacity	Up to 10 gpm @ 2000 psi (38 lpm @ 138 bar)
Operating Weight	1290 lbs (585 kg)
Travel Speed	2 mph (3.2 km/h)
Hydraulic Circuit	See Order Information
System Relief Pressure	2500 psi (172 bar)
Reservoir Capacity	4.5 gal (17 liters)



Model MHP12211000 Shown

Order Information

- MHP11111000, 8 gpm/30 lpm Briggs & Stratton
- MHP12211000, 2, 5 gpm or 1, 10 gpm/2, 20 lpm or 1, 38 lpm Circuits Honda

Included Equipment

- Couplers
- Couplers