

MS-51M Magnetic Stirrers (Multi Position)

Manufacturer:

SKU#: 8194-10-0836



- User-friendly operation and time setting modes allowing various ways of multi-position stirring to meet users demands: single point, multiple point, whole row, whole column, etc.
- Easy-to-read VFD and intuitive control panel.
- Bright and vivid LED position indicating lamps.
- Non-slip see-through silicon plate mat. (optional)
- Chemical-resistant #304 grade stainless steel top-plate.
- Uncompromising safety devices.
- Best-in-the-class with broad speed range and suitable for high-speed rotation experimental environment.
- Ergonomic designed, lightweight, easy to operate, and low profile.
- Wide top plate.
- Non-slip strength rubber feet.
- Sparkless, silent and durable BLDC motor.
- Built-in thermal shutdown and current limit protection.

Product Description

The MIKRO 220R CELL CULTURE PACKAGE arrives with (3 each) adapters for standard 15mL and 50mL tissue culture tubes. What is not to like about the versatile and reliable MIKRO 220R microliter centrifuge. PACKAGE CONTENTS(1) Model 220R Refrigerated Centrifuge, (1) Fixed-angle Rotor, (6) Adapters 15 mL, (3) Adapters 50 mL, power cord. The Hettich MIKRO 220R tabletop microliter centrifuges can additionally used for centrifugation tasks such as PCR, DNA & RNA with the appropriate 24 or 48 place (optional) rotor. Great if you have a dynamic lab running multiple applications? For additional peace of mind, Hettich centrifuges come with a Five (5) Year Warranty. For quick and easy ordering be sure to view our MIKRO 220 centrifuge packages. Our centrifuge bundles ship complete with all the components to perform your applications effortlessly. Hettich Packages include a centrifuge, rotor, buckets, adapters and bio-containment lids (when applicable). As always, Hettich ships fast, within 48 hours.

MS-51M Magnetic Stirrers (Multi Position) Specification

Model	MS-23M	MS-32M	MS-33M
Technical Data	Speed Control	Feedback control with PID	
Stirring	Positions	6	6
Speed Range (RPM)	30 to 2,000		
Stirring Point Distance (mm / inch, W D)	117 170 / 4.6 6.69	117 90 / 4.6 3.54	117 90 / 4.6 3.54
Timer	1 min. to 99 hours 59 min.		
Speed Display	VFD		
Motor Rating Input / Output (W)	2.9 / 1.6		

Load, Max (kg / lbs)	30 / 66.14		
General Data	Dimension (mm / inch, W D H)	377 434 81 / 14.84 17.09 3.19	254 434 81 / 10 17.09 3.19
Weight (kg / lbs)	6 / 13.23	5 / 11.02	7 / 15.43
Electrical Requirements	AC 100 ~ 240V, 50 / 60Hz		
Power Consumption (W)	45	45	54
Protection Class (DIN EN 60529)	IP 21		
Cat. No.	KR plug	AAH332115K	AAH332215K
US plug	AAH332115U	AAH332215U	AAH332315U

WHY BUY FROM GMI?

Your trusted source for Used & New lab equipments, Parts, Factory Clearance instrument service since 1985.



**TRADE IT.
UPGRADE IT.**

We routinely save discerning laboratories 50-80% off retail on our recertified instrument offerings.

Quality? ISO 9001:2008 certified means we remove 100% of the risk in buying 'used' laboratory equipment.

Warranties from 90 days to a year as well as multi-year service agreements are available.

GMI is an industry-leading distributor of brand new laboratory equipment and instruments. We supply a wide range of cutting-edge analytical instruments including centrifuges, gas chromatographs, freezers, thermal cyclers, and more. Choose from more than a thousand of new and innovative lab instruments that meet specifications and come with warranties up to 1 year.

