

**General attributes**

Approvals / Conformity  
Enclosure Type per IEC 60529  
Indicator actuators supply UA  
Indicator IO-Link comm.  
Mounting instruction  
Scope of delivery  
Transmission protocol

CE  
IP67 (when connected)  
Yes, LED green  
Yes, LED green  
See short guide  
Short guide  
IO-Link 1.1

**Electrical attributes**

Configurable in-/outputs  
Cycle time min.  
Eff. operating voltage Ue DC  
Indicator modul supply  
IO-Link  
IO-Link Specification

No  
5.5 ms  
24 V  
Yes, LED green  
Device  
1.1

Number of IO-Link ports

1


Number of outputs  
Operating voltage UB max. DC [V]  
Operating voltage UB min. DC [V]  
Process data cycle  
Transfer rate

24 (with 300 mA)  
30.2 V  
18 V  
5.5 ms at cycle time min.  
COM2 (38.4 kBaud)

**Mechanical attributes**

Ambient temperature Ta max.  
Ambient temperature Ta min.  
Cable length  
Frametype  
Housing material  
Housing shield  
Storage temperature max.  
Storage temperature min.

55 °C  
-5 °C  
0.50 m  
2.V  
Al  
No  
70 °C  
-25 °C



IO-Link  
PIN 1: +24 V, US  
PIN 2: +24 V, UA  
PIN 3: GND  
PIN 4: C/Q, IO-Link DC-Channel