



Aluminium Storz Couplings

Sizes: 1/2" to 8"

Materials: Aluminium Alloy
Optional Materials of Stainless Steel and Brass available

Pressure: Maximum working pressure 16 bar/232 psi


Details: Both halves of the coupling are of an identical design with no separate male or female halves. Either half can, therefore, be connected to any similar size of coupling. The hose coupling can be connected to another style, e.g.: hose tail, female or male threaded and blanking caps. It is essential that the distance between locking ears (KA) is the same on all fittings



SUCTION COUPLINGS


| PART NO. | NOMINAL SIZE | D (mm) | KA (mm) | L (mm) |
|--------------|--------------------------------|--------|---------|--------|
| 2/D-25 AL | Storz 25 (D) = DIN 14301 | 25 | 31 | 50 |
| 2/32-19 AL | Storz 32 | 19 | 44 | 65 |
| 2/32-25 AL | Storz 32 | 25 | 44 | 65 |
| 2/32-32 AL | Storz 32 | 32 | 44 | 75 |
| 2/38-38 AL | Storz 38 | 38 | 52 | 75 |
| 2/C-32 AL | Storz 52 (C) | 25 | 66 | 90 |
| 2/C-38 AL | Storz 52 (C) | 32 | 66 | 90 |
| 2/C-45 AL | Storz 52 (C) | 45 | 66 | 90 |
| 2/C-52 AL | Storz 52 (C) = DIN14321 | 52 | 66 | 90 |
| 2/C-60 AL | Storz 52 (C) | 60 | 66 | 125 |
| 2/65-65 AL | Storz 65 | 65 | 81 | 90 |
| 2/B-65 AL | Storz 75 (B) | 65 | 89 | 125 |
| 2/B-70 AL | Storz 75 (B) | 70 | 89 | 95 |
| 2/B-75 AL | Storz 75 (B) = DIN 14322 | 75 | 89 | 125 |
| 2/B/80 AL | Storz 75 (B) | 80 | 89 | 135 |
| 2/90 AL | Storz 90 | 90 | 105 | 150 |
| 2/100 AL | Storz 100 | 100 | 115 | 120 |
| 2/A-100 AL | Storz 110 (A) | 100 | 133 | 170 |
| 2/A-110 AL | Storz 110 (A) = DIN 14323 | 110 | 133 | 170 |
| 2/125 AL | Storz 125 | 125 | 148 | 196 |
| 2/135-135 AL | Storz 135 | 135 | 159 | 196 |
| 2/150-150 AL | Storz 150 = F (3 Claws) Forged | 150 | 160 | 180 |
| 2/165-150 AL | Storz 165 | 150 | 188 | 275 |
| 2/205 AL | Storz 205 | 205 | 220 | 375 |
| 96 | Storz Spanner | - | - | - |

Rubber Seals (suitable for Petrol and Oil Fluids)




| BSP FEMALE THREADED ADAPTERS | | | | |
|------------------------------|--------------------------------|-------------|------------|-----------------|
| PART NO. | NOMINAL SIZE DIN ISO 228 | PIPE THREAD | KA (mm) | MATERIAL |
| 3/D-050 AL | Storz 25 (D) - DS* | 1/2" | 31 | Aluminium Alloy |
| 3/D-075 AL | Storz 25 (D) - DS* | 3/4" | 31 | Aluminium Alloy |
| 3/D-100 AL | Storz 25 (D) - DS* = DIN14306 | 1" | 31 | Aluminium Alloy |
| 3/32-100 AL | Storz 32 - DS* | 1" | 44 | Aluminium Alloy |
| 3/32-125 AL | Storz 32 - DS* | 1 1/4" | 44 | Aluminium Alloy |
| 3/38-150 AL | Storz 38 - DS* | 1 1/2" | 52 | Aluminium Alloy |
| 3/38-200 AL | Storz 38 - DS* | 2" | 52 | Aluminium Alloy |
| 3/C-100 AL | Storz 52 (C) | 1" | 66 | Aluminium Alloy |
| 3/C-125 AL | Storz 52 (C) | 1 1/4" | 66 | Aluminium Alloy |
| 3/C-150 AL | Storz 52 (C) | 1 1/2" | 66 | Aluminium Alloy |
| 3/C-200 AL | Storz 52 C = DIN14307 | 2" | 66 | Aluminium Alloy |
| 3/C-250 AL | Storz 52 (C) | 2 1/2" | 66 | Aluminium Alloy |
| 3/65-200 AL | Storz 65 | 2" | 81 | Aluminium Alloy |
| 3/65-250 AL | Storz 65 | 2 1/2" | 81 | Aluminium Alloy |
| 3/B-200 AL | Storz 75 (B) | 2" | 89 | Aluminium Alloy |
| 3/B-250 AL | Storz 75 B = DIN 14308 | 2 1/2" | 89 | Aluminium Alloy |
| 3/B-300 AL | Storz 75 (B) | 3" | 89 | Aluminium Alloy |
| 3/90-300 AL | Storz 90 | 3" | 105 | Aluminium Alloy |
| 3/100-400 AL | Storz 100 - DS* | 4" | 115 | Aluminium Alloy |
| 3/A-400 AL | Storz 110 (A) | 4" | 133 | Aluminium Alloy |
| 3/A-450 AL | Storz 110 A = DIN 14309 | 4 1/2" | 133 | Aluminium Alloy |
| 3/125-500 AL | Storz 125 | 5" | 148 | Aluminium Alloy |
| 3/150-600 AL | Storz 150 = F (3 Claws) Forged | 6" | 160 | Aluminium Alloy |
| 3/165-600 AL | Storz 165 | 6" | 188 | Aluminium Alloy |
| 3/165-700 AL | Storz 165 | 7" | 188 | Aluminium Alloy |
| 3/205-800 AL | Storz 205 | 8" | 220 | Aluminium Alloy |
| 96 | Storz Spanner | - | - | - |

*DS - Suitable for both pressure and suction couplings




| BSPP MALE THREADED ADAPTERS | | | | |
|-----------------------------|-----------------------------|-------------|------------|-----------------|
| PART NO. | NOMINAL SIZE DIN ISO 228 | PIPE THREAD | KA (mm) | MATERIAL |
| 4/D-100 AL | Storz 25 (D) - DS* | 1" | 31 | Aluminium Alloy |
| 4/D-32-100 AL | Storz 32 DS* | 1" | 44 | Aluminium Alloy |
| 4/32-125 AL | Storz 32 DS* | 1 1/4" | 44 | Aluminium Alloy |
| 4/38-150 AL | Storz 38 - DS* | 1 1/2" | 52 | Aluminium Alloy |
| 4/C-125 AL | Storz 52 (C) | 1 1/4" | 66 | Aluminium Alloy |
| 4/C-200 AL | Storz 52 (C) | 2" | 66 | Aluminium Alloy |
| 4/B-250 AL | Storz 75(B) | 2 1/2" | 89 | Aluminium Alloy |
| 4/B-300 AL | Storz 75(B) | 3" | 89 | Aluminium Alloy |
| 4/A-400 AL | Storz 110(A) | 4" | 133 | Aluminium Alloy |

*DS - Suitable for both pressure and suction couplings




REDUCERS STORZ - STORZ (SWIVEL)

| PART NO. | KA x KA (mm) | | MATERIAL |
|----------|-------------------|--------|-----------------|
| 7/C-D AL | C - D = DIN 14341 | 66/31 | Aluminium Alloy |
| 7/B-C AL | B - C = DIN 14342 | 89/66 | Aluminium Alloy |
| 7/A-B AL | A - A = DIN 14343 | 133/89 | Aluminium Alloy |



REDUCERS STORZ - STORZ (RIGID)

| PART NO. | KA x KA (mm) | | MATERIAL |
|------------|--------------|---------|-----------------|
| 7/C-38 AL | Storz C-38 | 66/52 | Aluminium Alloy |
| 7/C-32 AL | Storz C-32 | 66/44 | Aluminium Alloy |
| 7/65-C AL | Storz 65-C | 81/66 | Aluminium Alloy |
| 7/B-65 AL | Storz B-65 | 89/81 | Aluminium Alloy |
| 7/90-B AL | Storz 90-B | 105/89 | Aluminium Alloy |
| 7/100-B AL | Storz 100-B | 115/89 | Aluminium Alloy |
| 7/A-100 AL | Storz A-100 | 133/115 | Aluminium Alloy |
| 7/125-A AL | Storz 125-A | 148/133 | Aluminium Alloy |
| 7/150-A | Storz 150-A | 160/133 | Aluminium Alloy |



BLANK CAPS WITH CHAIN

| PART NO. | NOMINAL SIZE | KA (mm) | MATERIAL I.D. of coupling |
|----------|--------------------------------|---------|------------------------------|
| 8/D AL | Storz 25 D - DS* = DIN 14310 | 31 | Aluminium Alloy |
| 8/32 AL | Storz 32 DS* | 44 | Aluminium Alloy |
| 8/38 AL | Storz 38 DS* | 52 | Aluminium Alloy |
| 8/C AL | Storz 52 C = DIN 14311 | 66 | Aluminium Alloy |
| 8/65 AL | Storz 65 | 81 | Aluminium Alloy |
| 8/B AL | Storz 75 B = DIN 14312 | 89 | Aluminium Alloy |
| 8/90 AL | Storz 90 | 105 | Aluminium Alloy |
| 8/100 AL | Storz 100 - DS* | 115 | Aluminium Alloy |
| 8/A AL | Storz 110 A = DIN 14313 | 133 | Aluminium Alloy |
| 8/125 AL | Storz 125 | 148 | Aluminium Alloy |
| 8/150 AL | Storz 150 = F (3 Claws) forged | 160 | Aluminium Alloy |
| 8/165 AL | Storz 165 | 188 | Aluminium Alloy |
| 8/205 AL | Storz 205 | 220 | Aluminium Alloy |
| 96 | Storz Spanner | - | - |

*DS - Suitable for both pressure and suction couplings



DELIVERY-SUCTION SEALS

| PART NO. | |
|-----------|-------------------------|
| 69/D PB | Storz 25 D* = DIN 14301 |
| 69/32 PB | Storz 32 - DS* |
| 69/38 PB | Storz 38 - DS* |
| 69/CPB | Storz 52 C = DIN 14311 |
| 69/C FQ | Food Quality |
| 69/65 PB | Storz 65 |
| 69/BPB | Storz 75 B = DIN 14312 |
| 69/B FQ | Food Quality |
| 69/90 PB | Storz 90 |
| 69/90 FQ | Food Quality |
| 69/100 PB | Storz 100 - DS* |
| 60/100 FQ | Food Quality |
| 69/A PB | Storz 110 A = DIN 14313 |
| 69/A FQ | Food Quality |
| 69/125 PB | Storz 125 |

**DS - Suitable for both pressure & suction couplings.*

Food quality material available on request.