


TEL-TRU PRESSURE TRANSMITTERS

Industrial Silicon Glass Fused Threaded Series — Model P611

Ordering Example: Glass Fused Pressure Transmitter, threaded, 4-20mA output, 0.5% accuracy, 0-100 psi, gauge pressure, 1/4"-18 NPT male, 2' vented PVC cable



Code	Description	Price
A	P611 Industrial Press. Transmitter	\$253.58
B	Output	
A	4-20mA (2-wire), 10-30Vdc exc.	N/C
C	Accuracy Includes linearity (BFSL), hysteresis, repeatability	
2	+/-0.50%	N/C
3	+/-0.25%	44.10
5	+/-0.15% (4-20mA only)	88.20
D	Pressure Range (all available for both models) Additional pressure ranges/units of measure available on request.	
Code	Calib. Range	Code Calib. Range N/C
B7A	0 to 15psi	H2A 0 to 1,500psi
C6A	0 to 30psi	H5A 0 to 2,000psi
D6A	0 to 60psi	H9A 0 to 3,000psi
D9A	0 to 100psi	J4A 0 to 4,000psi
E3A	0 to 150psi	J8A 0 to 5,000psi
E5A	0 to 200psi	K2A 0 to 7,500psi
E8A	0 to 300psi	K4A 0 to 10,000psi
F3A	0 to 500psi	V6A 3 to 15psi
F6A	0 to 750psi	V7A 3 to 27psi
F8A	0 to 1,000psi	
E	Mode	
G	Gauge Pressure Ref.	N/C
F	Process Connection	
03	1/2"-14NPT Male	16.54
01	1/4"-18NPT Male	16.54
02	1/4"-18NPT Female	22.05
05	1/8"-27NPT Male	16.54
06	1/8"-27NPT Female	22.05
07	7/16"-20UNF Male	16.54
66	7/16"-20UNF Female	N/C
10	BSPP 1/4-19 (G1/4) Male	16.54
57	BSPP 1/2 (G1/2) Male	16.54

Code	Description	Price
G	Electrical Connection	
D100	Mini-DIN 43650 C (w/mate) - IP65	N/C
D200	Std. DIN 43650 A (w/mate) - IP65	N/C
G302	2' vented PVC cable	11.03
G305	5' vented PVC cable	19.85
G502	2' vented poly. cable - (IP69K SS Strain Relief)	66.15
G505	5' vented poly. cable - (IP69K SS Strain Relief)	74.97
G402	1/2"NPT Male Conduit Conn. (w/2' vented PVC cable)	33.08
G405	1/2"NPT Male Conduit Conn. (w/5' vented PVC cable)	38.59
	<i>Request quote for more than 5' cable</i>	
H	Options	
K2	Orifice Restrictor for press. spike suppression within process conn., 0.3mm orifice	16.54
B3	Oxygen Cleaning	RFQ
M2	Local LED display (requires DIN 43650A conn. and 4-20mA electronics (also sold sep. as PTD-2))	252.00

Note: Prices include Certificate of Calibration (directly traceable to NIST), which includes three check points.

Accessories (order separately)

Code	Description	Price
PTD-2	4-20m local transmitter display (also sold as option M2 above)	252.00
10000004-PT	Cert. of Origin & Compliance	22.05
10000003-PT5	Certified Calibration (traceable to NIST), five check points	55.13
	Right Angle Shielded PVC cordsets w/free leads, non-vented, for pressure ranges > 0-300psi	
96011501	M12x1 4-pin, 2 meters	52.50
96011601	M12x1 4-pin, 5 meters	65.63

