

**Product Information**

# Additional Devices For GK / GKL

## GKEH-1256 / GKEL-1257

for types GK-010 / GK-015 / GK-020



**Technical data**

<b>Switch/sensor</b>	bistable reed switch (grid)	
<b>Wiring</b>	GKEH-1256 maximum limit value transmitter normally open (n.o.) No. 0.372	GKEL-1257 minimum limit value transmitter normally closed (n.c.) No. 0.441
<b>Switching voltage</b>	max. 250 V AC	
<b>Switching current</b>	max. 0.2 A	
<b>Switch performance</b>	max. 10 VA	
<b>Protection class</b>	2 - safety insulation	
<b>Ingress protection</b>	IP 65	
<b>Connection</b>	DIN 43650-B plug	
<b>Non-medium-contact materials</b>	PBTP, PA	
<b>Weight</b>	0.035 kg	

## GKEH-1251 / GKEL-1252

for types GK-025 / GKL



**Technical data**

<b>Switch/sensor</b>	bistable reed switch (grid)	
<b>Wiring</b>	GKEH-1251 maximum limit value transmitter normally open (n.o.) No. 0.372	GKEL-1252 minimum limit value transmitter normally closed (n.c.) No. 0.441
<b>Switching voltage</b>	max. 250 V AC	
<b>Switching current</b>	max. 0.2 A	
<b>Switching capacity</b>	max. 10 VA	
<b>Protection class</b>	2 - safety insulation	
<b>Ingress protection</b>	IP 65	
<b>Connection</b>	DIN 43650-B plug	
<b>Non-medium-contact materials</b>	PBTP, PA	
<b>Weight</b>	0.075 kg	

## GKK-1270 / 1271 GKI-1272 / 1273 / 1273-1



**GKK**

GKK-1271 for types GK-  
 GKK-1270 for types GKL-

**Technical data**

<b>Switch/sensor</b>	reed switch chain
<b>Wiring</b>	no. 0.451
<b>Supply voltage</b>	max. 24 V DC
<b>Output signal</b>	0..10 kOhm
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg

**GKI**

GKI-1273 for types GK-010 / GK-015 / GK-020  
 GKI-1273-1 for types GK-025  
 GKI-1272 for types GKL-

**Technical data**

<b>Switch/sensor</b>	reed switch chain with integrated 2-wire transducer
<b>Wiring</b>	no. 0.452
<b>Supply voltage</b>	11..40 V depending on the load
<b>Load</b>	max. 1500 Ohm
<b>Output signal</b>	4..20 mA
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg

Product Information

**Additional Devices For GK**

GKEH-1256 / GKEL-1257



Technical data

<b>Switch/sensor</b>	bistable reed switch (grid)	
<b>Wiring</b>	GKEH-1256 maximum limit value transmitter normally open (n.o.) No. 0.372	GKEL-1257 minimum limit value transmitter 'normally closed' No. 0.441
<b>Switching voltage</b>	max. 250 V AC	
<b>Switching current</b>	max. 0.2 A	
<b>Switching capacity</b>	max. 10 VA	
<b>Protection class</b>	2 - safety insulation	
<b>Ingress protection</b>	IP 65	
<b>Connection</b>	DIN 43650-B plug	
<b>Non-medium-contact materials</b>	PBTP, PA	
<b>Weight</b>	0.08 kg	

GKEH-1251 / GKEL-1252

for types GK-025



Technical data

<b>Switch/sensor</b>	bistable reed switch (grid)	
<b>Wiring</b>	GKEH-1251 maximum limit value transmitter normally open (n.o.) No. 0.372	GKEL-1252 minimum limit value transmitter normally closed (n.c.) No. 0.441
<b>Switching voltage</b>	max. 250 V AC	
<b>Switching current</b>	max. 0.2 A	
<b>Switching Capacity</b>	max. 10 VA	
<b>Protection class</b>	2 - safety insulation	
<b>Ingress protection</b>	IP 65	
<b>Connection</b>	DIN 43650-B plug	
<b>Non-medium-contact materials</b>	PBTP, PA	
<b>Weight</b>	0.08 kg	

GKK-1271 / GKI-1273 / 1273-1



GKK-1271

Technical data

<b>Switch/sensor</b>	reed switch chain
<b>Wiring</b>	No. 0.451 
<b>Supply voltage</b>	max. 24 V DC
<b>Output signal</b>	0..10 kOhm
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg

GKI

GKI-1273 for types GK-010 / GK-015 / GK-020  
 GKI-1273-1 for types GK-025

Technical data

<b>Switch/sensor</b>	reed switch chain with integrated 2-wire transducer
<b>Wiring</b>	no. 0.452 
<b>Supply voltage</b>	11..40 V depending on the load 
<b>Load</b>	max. 1500 Ohm
<b>Output signal</b>	4..20 mA
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg

Product Information

# Additional Devices For GKL

GKEH-1251 / GKEL-1252



Technical data

<b>Switch/sensor</b>	bistable reed switch (grid)	
<b>Wiring</b>	GKEH-1251 maximum limit value transmitter normally open (n.o.) No. 0.372	GKEL-1252 minimum limit value transmitter normally closed (n.c.) No. 0.441
<b>Switching voltage</b>	max. 250 V AC	
<b>Switching current</b>	max. 0.2 A	
<b>Switching capacity</b>	max. 10 VA	
<b>Protection class</b>	2 - safety insulation	
<b>Ingress protection</b>	IP 65	
<b>Connection</b>	DIN 43650-B plug	
<b>Non-medium-contact materials</b>	PBTP, PA	
<b>Weight</b>	0.08 kg	

GKK-1270 / GKI-1272



GKK-1270

Technical data

<b>Switch/sensor</b>	reed switch chain
<b>Wiring</b>	no. 0.451 
<b>Supply voltage</b>	max. 24 V DC
<b>Output signal</b>	0..10 kOhm
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg

GKI-1272

Technical data

<b>Switch/sensor</b>	reed switch chain with integrated 2-wire transducer
<b>Wiring</b>	no. 0.452 
<b>Supply voltage</b>	11..40 V depending on the load 
<b>Load</b>	max. 1500 Ohm
<b>Output signal</b>	4..20 mA
<b>Protection class</b>	2 - safety insulation
<b>Ingress protection</b>	IP 65
<b>Connection</b>	DIN 43650-B plug
<b>Non-medium-contact materials</b>	ABS, PA
<b>Weight</b>	0.1 kg