

Lubri-Cup™ VG Mini

Automatic single-point lubricator dispenses Chesterton grease to critical areas, eliminating over and under greasing.

User Friendly

- A compact, convenient and sturdy design that is simple to install and operate.

Equipment Friendly

- Designed for precise and reliable Lubrication. Chesterton's industrial greases offer extended bearing life and reliability even under the harshest conditions of load, temperature, water and corrosion.

Cost Effective

- Simple yet cost effective unit.

Safe

- Internal Pressure relief system for added safety.
- Non flammable, thermally stable nitrogen gas



Five different preset dispensing rates: 1, 3, 6, 9, 12 months

Electrochemical operation (Nitrogen Gas)

Transparent container for lubricant inspection

Instant ON & OFF available

Packaging: 10 units/case

Specifications	
Grease Capacity	120ml
Operating temperature	-20°C - 55°C (-4°F - 131°F)
Max Operating Pressure	5 bar (70psi)
Installation thread size	1/4" PT resilient plastic NPT & BSPT compatible
Remote installation	Up to 0.3m(1ft) using a 8mm(5/16") OD pre-filled lube line
Certifications / IP code:	CE / IP65

Order Numbers

Lubri-Cup™ VG Mini with 630 SXCF Grease	084473
---	--------