

# Juice Dispenser



# Postmix Dispenser FSD3000

## Specifications

- Exterior covering and door: galvanized sheet steel, coated in silver
- Illuminated display as standard
- Lockable as standard
- Constant, easy adjustable brix value
- Big drip tray, grid, cup locator

## Technical data

- Dispensing capacity 60 l per hour
- Cooling capacity 725 W ( $t_0 = 0\text{ }^\circ\text{C}$ )
- Power consumption 2,3 A
- Electrical fuse 16 A
- Refrigerant R134a / 0,21 kg
- Water pressure mind. 3 up to 7 bar



FSD3000-2

2 lines for juice, 1 line for water  
 Weight 64 kg  
 Measurements (W x D x H): 320 x 580 x 910 mm

2.350,00 €

FSD3000-3

3 lines for juice, 1 line for water  
 Weight 74 kg  
 Measurements (W x D x H): 440 x 580 x 910 mm

3.120,00 €

Options

FSD3000OW	Without water line	-50,00 €
FSD3000OD	Flat stainless steel door instead of illuminated display	-230,00 €
FSELD	Elektrical portion control, time controlled, for max. 4 lines (incl. water), portions adjustable	370,00 €
FSDAUTCLEAN	Self-cleaning as function, before and after tap process, only with FSELD available	72,00 €
FSDPUMP	PROCON-Pump with Motor (ONLY for FSD3000-4)	260,00 €
FSDJEX	Jug extension instead of drip tray to fill decanters and jugs. New height of the dispenser: 1050 mm	195,00 €
FSDRD	Illuminated display on the back of the machine	390,00 €



FSD3000-4

4 lines for juice, without water	3.610,00 €
Weight 84 kg	
Measurements (W x D x H): 520 x 580 x 960 mm	



FSD3000-JuiceTower

FSD3000-3U	640,00 €
Cabinet in st. steel, 4 castors	
Prepared for pump and water containers	
FSD3000-3	3.120,00 €
3 juice lines, 1 water line	

# Postmix Dispenser FSD3100 EcoLine

## Specifications

- Exterior covering and door: galvanized sheet steel, coated in silver
- Lockable as standard
- Integral switch for blocking the push buttons
- Standard and flow cooling
- Feet 60 mm
- Big drip tray, grid, cup locator (removable and dishwasher safe)

## Technical data

- Dispensing capacity 30 l per hour
- Cooling capacity 350 W ( $t_0 = 0^\circ\text{C}$ )
- Power supply 220/230 V / 50 Hz
- Power consumption 1,3 A
- Elektrical Fuse 16 A
- Refrigerant R134a / 0,11 kg
- Water pressure min. 3 up to 7 bar
- Water connection 3/4" – 3/8", 1,5 m



FSD3100E-2x10  
+ water (FSD3000-W)



FSD3100E-3x10  
+ water (FSD3000-W)  
+ LED Display

### FSD3100E-2x10

2 lines for juice, for 2 x 10 l bags, without water,	1.820,00 €
Weight 46 kg	
Measurements (W x D x H): 320 x 550 x 860 mm	

### FSD3100E-3x5

3 lines for juice, for 3 x 5 l bags, without water,	2.270,00 €
Weight 46 kg	
Measurements (W x D x H): 320 x 550 x 860 mm	

### FSD3100E-3x10

3 lines for juice, for 3 x 10 l bags, without water,	2.600,00 €
Weight 65 kg	
Measurements (W x D x H): 445 x 550 x 860 mm	

## Options

FSD3000-W	With water line	64,00 €
FSD3000-T	Door with illuminated display instead of a flat door in stainless steel	290,00 €