



Winpak Rotary Cup Machines

The perfect alternative for low product volumes typically associated with product launches, product development, and/or small food processors.







WSR ROTARY FILLING MACHINES

Winpak WSR Rotary Fill/Seal Cup Machines

Winpak WSR rotary cup machine is a flexible, low output fill/seal machine. The WSR is designed to run preformed round cups for a wide variety of product applications. Dependent upon the product application, the WSR rotary machine can produce up to 40 packages per minute. Flexible and right sized, the WSR rotary machine is ideal for small processors, product development programs, and product launches.

- ✓ Simple and flexible filling pump adjustment
- Easy changeover tooling available for alternate package sizes
- ✓ Wide range of product applications
- ✓ Outputs to match user needs
- ✓ Easy to operate
- ✓ Reliable



Market Leadership

Winpak is a leading supplier of fill/seal cup packaging machines for portion-control and single-serve applications. Winpak has been designing, fabricating, and supplying the food industry with fill/seal packaging systems for over 30 years. The WSR machine is an ideal market entry machine for portion control and single serve applications.

Applications include condiments, dips, sauces, salad dressings, cream cheese, sour cream, syrups, ketchup, margarine, butter, spreads, and many other liquid and semi-viscous products.

Winpak Means Total Packaging Solutions

Winpak is a recognized leader in creating packaging solutions for the food, dairy, beverage, healthcare, and industrial markets. Winpak provides total packaging solutions with innovative packaging machinery and high-quality packaging materials. Winpak also has a full support network of engineering and technical service professionals. Winpak has been providing complete packaging systems to companies worldwide for over 30 years.

- ✓ Innovative packaging machinery
- √ High-quality packaging materials
- Expert engineering and technical service



MACHINE INFORMATION

WSR-8 ROTARY FILLING MACHINE		
MACHINE SPECIFICATIONS		MACHINE FEATURES
Cup Rim Diameters:	51 mm, 60 mm, 70 mm, 75 mm, 80 mm	8 pockets Shut-off nozzles
Packaging Format:	Round preformed cups with individually die-cut foil lids	 Simple and flexible filling pump adjustment Stainless steel construction
Nominal Capacity:	Minimum = 0.375 fl. oz. (11 ml) Maximum = 8.0 fl. oz. (236 ml)	NEMA 4X industrial controls and enclosures Minimum maintenance
Cup Materials:	Polypropylene, Polypropylene Barrier, Polystyrene, Polystyrene Barrier	Filling temperatures are adaptable to product application
Lid Materials:	Variety of die-cut foil lidding materials	Packaging versatilityWide range of product applications
Product Applications:	Condiments, dips, sauces, salad dressings, cream cheese, sour cream, syrups, ketchup, dry snacks, and many other liquid and semi-viscous products	 PLC automated Touchscreen operator interface Adjustable PID temperature controller
Machine Format:	Rotary	Ideal low output filling machineSingle operator
Production Speed:	Variable up to 40 packages/minute (Dependent upon product application)	Changeover tooling for alternate cup diametersSmall footprint
Electrical Power:	208/230 VAC, 1 Phase, 15 Amps (Alternative electrical power available)	OPTIONS
Air:	Nominal = 3 scfm (1,416 cm ³ /sec) @ 90 psi (620 kPa) Minimum Pressure = 80 psi (551 kPa)	 Overcapping station Date coding on side of cups or on lids
Dimensions:	40" L x 30" W x 65" H (without conveyor) (1 m x .8 m x 1.7 m)	Take-off conveyors of different sizes and configurations
Uncrated Weight:	750 lbs. (340 kg)	Product tank level controlNitrogen flush

Nominal container capacity is from the fill line.

All sales are subject to Winpak's general terms and conditions.

All specifications are approximate and may vary slightly with options. Refer to the system drawings.