

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name Britesorb XLC

Synthetic amorphous silica

Use Beverage processing.

Manufacturer/Supplier: PQ Corporation

P.O. Box 840 Valley Forge PA 19482 USA

E-mail: sds.uk@pqcorp.com Telephone: +1 610-651-4200

Emergency Phone No. +1 800-424-9300

2. HAZARDS IDENTIFICATION

EC Classification Not classified as dangerous for supply/use.

Exposure to any kind of dust is potentially harmful.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	%W/W	CAS No.	EINECS	EC Classification
			No.	
Synthetic amorphous silica	> 80 %	112926-00-8	2315454	Occupational Exposure Limits
Water	< 20 %	7732-18-5	2317912	

4. FIRST AID MEASURES

Eye Contact If substance has got into the eyes, immediately wash out with plenty

of water. Obtain immediate medical attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop,

obtain medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water. If large amount

swallowed or symptoms develop obtain medical attention.

Inhalation Remove patient from exposure, keep warm and at rest. If symptoms

develop, obtain medical attention.

5. FIRE-FIGHTING MEASURES

General: Not applicable. Inorganic powder or granules. Non-combustible.

Revision: v6 Date: 05/2010 MSDS 0051100 Page: 1 of 4

Ref: 1080



6. ACCIDENTAL RELEASE MEASURES

Personal Protection Wear suitable protective clothing. Wear eye/face protection.

An approved dust mask should be worn if dust is generated during

handling.

See Also Section 8.

General: Contain spillages. Dampening with water can reduce dust. Sweep

or preferably vacuum up and collect in suitable containers for

recovery or disposal.

7. HANDLING AND STORAGE

Handling Avoid generation of dust.

See Also Section 8.

A considerable static electrical charge can be built up during mechanical handling which may become a hazard in atmospheres containing flammable vapours. Advice on the control of static is

given in British Standard BS 5958.

Storage Keep container tightly closed and dry.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Synthetic amorphous silica Silica amorphous, total inhalable dust: UK EH40: WEL 6 mg/m3 8h

TWA

Silica amorphous, respirable dust: UK EH40: WEL 2.4 mg/m3 8h

TWA.

Silica, Amorphous - Precipitated silica and silica gel: ACGIH: TLV

withdrawn 2006

General: Engineering methods to prevent or control exposure are preferred.

Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process

conditions.

Respirators Avoid inhalation of dusts. Wear suitable respiratory protective

equipment if working in confined spaces with inadequate ventilation or where there is any risk of the exposure limits being exceeded. Advice on respiratory protective equipment is given in the HSE

(Health and Safety Executive) publication HS(G)53.

Skin Contact Wear suitable protective clothing and gloves. Plastic or rubber

gloves. For example EN374-3. Wear suitable overalls.

Eye Protection Safety spectacles. Goggles.

Other Wear protective equipment to comply with good occupational

hygiene practice.

Do not eat, drink or smoke at the work place.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Powder.
Colour White.
Odour Odourless.

pH (Value) 3 - 10 at 5% w/w in water.

Melting Point (°C) > 1000

Flash Point (°C) [Closed cup] Not applicable. Flammable Limits (Lower) Not applicable.

(%v/v)

Revision: v6 Date: 05/2010 MSDS 0051100 Page: 2 of 4

Ref: 1080



Solubility (Water) Insoluble.

STABILITY AND REACTIVITY *10.*

Stability This product is hygroscopic.

Hazardous Reactions Hazardous Decomposition

Product(s)

None known. None known.

11. TOXICOLOGICAL INFORMATION

The lethal dose for humans for synthetic amorphous silica is **Acute Toxicity**

estimated at over 15000 mg/kg.

Synthetic amorphous silica is a permitted food additive in the UK,

US and many other countries.

Inhalation Synthetic amorphous silica has little adverse effect on lungs and

does not produce significant disease or toxic effect when exposure is kept below the permitted limits. However, existing medical conditions (eg. asthma, bronchitis) may be aggravated by exposure to dust. Effects of dust may be greater, and occur at lower levels of

exposure in smokers compared to non-smokers. Dust may cause discomfort and mild irritation.

Eye Contact Skin Contact Dust may have a drying effect on the skin.

IARC assessment: Amorphous silica is not classifiable as to its **Carcinogenicity Information**

carcinogenicity to humans (Group 3).

12. **ECOLOGICAL INFORMATION**

Synthetic amorphous silica is virtually inert and has no known **Ecotoxicity**

adverse effect on the environment.

13. **DISPOSAL CONSIDERATIONS**

Recommended: Disposal should be in accordance with local, state or national

legislation.

This product normally causes no problems in sewage treatment

works, where it settles with the sewage sludge.

This material is not classified as hazardous waste under EEC Directive 91/689/EEC (and amendments). This material is not classified as hazardous waste under the Hazardous Waste

(England and Wales) Regulations SI 2005 No. 894.

May be disposed of by landfill in accordance with local regulations.

TRANSPORT INFORMATION *14*.

Not classified according to the United Nations 'Recommendations on the Transport of Dangerous Goods'.

Packaging No special packaging requirements.

Revision: v6 MSDS 0051100

Ref: 1080

Date: 05/2010

Page: 3 of 4





15. REGULATORY INFORMATION

EC Classification Not classified as dangerous for supply/use.

Safety Phrases Handle in accordance with good industrial hygiene and safety

practices.

Avoid inhalation of dusts.

TSCA Inventory Status: Reported/Included. CAS No. 7631-86-9

AICS Inventory Status: Reported/Included. DSL/NDSL Inventory Status: Reported/Included.

FDA: Silicon dioxide 21CFR 172.480

16. OTHER INFORMATION

The following sections contain revisions or new statements: Section 1

MSDS first issued 11/02/1999 MSDS data revised 05/2010

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. PQ Corporation gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. PQ Corporation accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: v6 Date: 05/2010 MSDS 0051100 Page: 4 of 4

Ref: 1080