

# TECHNICAL SHEET

## COMPATTO 3000



|                                                 |                                                                                    |                                                                                            |                                                                   |                                                 |                                                  |                                                                    |
|-------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------|-------------------------------------------------|--------------------------------------------------|--------------------------------------------------------------------|
| COMPRESSORE<br>COMPRESSOR<br>COMPRESOR          | REFRIGERANTE<br>COOLANT<br>REFRIGERANTE                                            | POTENZA IN W - Kcal<br>POWER IN W - Kcal<br>POTENCIA EN W - Kcal                           | POTENZA ASSORBITA<br>absorbed power<br>potencia absorbida         | SERPENTINE<br>COILS<br>SERPENTINES              | VASCA DELL'ACQUA<br>WATER TANK<br>TANQUE DE AGUA | POMPA DI RICIRCOLO<br>RECIRCULATION PUMP<br>bomba de recirculación |
| <b>1/2+HP</b>                                   | <b>R404A</b>                                                                       | <b>1220w<br/>1049Kcal</b>                                                                  | <b>758w</b>                                                       | <b>1-3<br/>27-22MT</b>                          | <b>75lt.</b>                                     | <b>8/13<br/>Ø52.5</b>                                              |
| BANCO DI GHIACCIO<br>ICE BANK<br>BANCO DE HIELO | CAPACITA' DI<br>RAFFREDDAMENTO<br>COOLING CAPACITY<br>CAPACIDAD DE<br>ENFRIAMIENTO | TEMP. BEVANDA IN/OUT<br>IN/OUT TEMP. OF DRINK<br>TEMP. DE LA BEBIDA<br>EN ENTRADA Y SALIDA | EROGAZIONE MINUTO<br>RATE OF DRINK PER MIN.<br>SUBMIN. POR MINUTO | TENSIONE<br>VOLTAGE<br>TENSION                  | PESO NETTO<br>NET WEIGHT<br>PESO NETO            | CARROZZERIA<br>HOUSING<br>CARROCERÍA                               |
| <b>35kg</b>                                     | <b>180lt.<br/>hour</b>                                                             | <b>25C°<br/>6C°</b>                                                                        | <b>15x200<br/>cc</b>                                              | <b>220/240-50hz<br/>110v-60hz<br/>220v-60hz</b> | <b>57kg</b>                                      | <b>AISI430<br/>BASE IN<br/>AISI 304</b>                            |



# TECHNICAL SHEET

## COMPATTO 3000

