


## Product Line 603 (anti-swiveling)

## Product Line 610

dimensions in mm



**Outlet points easy to use for withdrawal of technical gases. To mount on wall for connection with a central gas supply system (ring line). The compact design is modular expandable and offers a variety of possible combinations.**

### Benefits

- gas paths and design features are customisable combinable
- inlet with fittings (soldering end and/or welding socket) and outlet with nozzle or male thread (option hose coupling)
- ball valves in inlets signals clearly position OPEN / CLOSED respectively gas flow / gas stop
- quick and easy wall mounting
- compact design
- completely mounted and tested
- up to max. 3 gas paths (610-3) see top figure

#### Product Line 603:

- nearly unlimited number of gas paths
- nickel plated tube with nickel plated wall screen, for withdrawal of acetylene, fuel gas, oxygen and shielding gas
- anti-swiveling fixing of pressure regulator / safety device

#### Product Line 610:

- stainless steel plate, for use of acetylene, fuel gas, oxygen and shielding gas

### Options

- pressure regulator with pressure gauge or flow meter
- model with safety devices, according to EN 730 / ISO 5175-1 against dangerous reverse gas flow and flashbacks
- hose coupling SK100 according to DIN EN 561 / ISO 7289
- WITTFIX-Pipe Couplers

### Operation / Usage

Outlet points are connected to the central gas supply system by ring or stub lines and concerted to the required local flow and customise operating pressures.

### Indication

603-1	respectively	610-1	for one gas path
603-2	respectively	610-2	for two gas paths
603-3	respectively	610-3	for tree gas paths
603-X			for more than tree gas paths

### Approvals

Company certified according to ISO 9001  
 Cleaned for Oxygen Service according to:  
 - EIGA IGC Doc 13/12/E: Oxygen Pipeline and Piping Systems

**Other models, options and accessories available on request.**

**Please identify the individual gases at the time of enquiring!**

# OUTLET POINTS 603 / 610



## Assembly:

Ball valve with male thread						
Gases	Acetylene	Fuel gas		Oxygen (burn-out safety)	Compressed air, Shielding Gas	
P <sub>V</sub> max. [bar]	1.5	40		40	40	
Nominal size	DN 10			DN 10	DN 10	
Connections	G 3/8 LH M with cone		G 3/8 RH M with cone		G 3/8 RH M with cone	
Pressure regulator						
Gases	Acetylene	Fuel gas		Oxygen	N <sub>2</sub> / Air	Shielding Gas with flow gauge / Shielding Gas with flow meter
P <sub>H</sub> max. [bar]	0 - 1,5	0 - 10	0 - 20*	0 - 10	0 - 20*	0 - 16 / 0 - 30 l/min
Connections	G 3/8 LH MT G 3/8 LH M with cone	G 3/8 LH MT G 3/8 LH M with cone	G 3/8 RH MT G 1/4 RH M with cone		G 3/8 RH MT G 1/4 RH M with cone	
Optional safety devices and hose couplings						
see data sheet ST 1, ST 2, ST 7, ST 9, ST 14 and SK 100						

\* option other P<sub>H</sub> on request

Order blank (please mark  the requested combination:

	<input type="checkbox"/> Product Line 603			<input type="checkbox"/> Product Line 610 (max. 3 Paths)	
	Path -1	Path -2	Path -3	Comments	
Gases from left to right					
<b>Inlet</b>					
for pipe Ø in [mm]					
for welding socket					
for soldering end					
for WITTFIX					
<b>Ball valve</b>					
DN 10					
<b>Pressure Regulator</b>					
pressure gauge [bar]					
flow gauge [l/min]					
flow meter [l/min]					
<b>Safety device</b>					
RF53N					
85-10					
Super 78					
Super 66					
Super 55					
Super 85					
<b>Outlet</b>					
nozzle for hose					
quick coupling SK100					