

E)	
Č)	

	CUSTOMER CONNECTIONS				
ITEM	DESCRIPTION	SIZE (100 PSI TRIM)	SIZE (15 PSI TRIM)	TYPE	
А	FEED WATER INLET	1/2"	1/2"	N.P.T.	
В	BLOWDOWN OUTLET	1"	1"	N.P.T.	
С	STEAM OUTLET	1 1/2"	3"	N.P.T.	
D	WATER COLUMN DRAIN	1"	1"	N.P.T.	
Е	SAFETY RELIEF VALVE	1 1/4"	1 1/4"	N.P.T.	

EQUIPMENT SPECIFICATION CHART			
TYPE:	ELECTRIC		
MAX ALLOWABLE WORKING PRESSURE:	100 PSI		
BOILER OUTPUT:	368,560 BTU/HR		
STEAM OUTPUT/MIN. SRV CAPACITY:	380 LBS/HR		
NUMBER OF ELEMENTS (WATTAGE PER ELEMENT):	6 (18 kW)		
WATER CAPACITY (OPERATING):	18 GAL.		
APPROXIMATE DRY WEIGHT:	423 LBS.		
APPROXIMATE OPERATING WEIGHT:	573 LBS.		
APPROXIMATE SHIPPING WEIGHT:	700 LBS.		
APPROXIMATE FLOODED WEIGHT:	656 LBS.		

ELECTRICAL REQUIREMENTS				
VOLTAGE	OPERATING FLA			
208/60/3	300 AMPS			
240/60/3	260 AMPS			
380/60/3	165 AMPS			
480/60/3	130 AMPS			
600/60/3	104 AMPS			

NOTE: OPERATING FULL LOAD AMPERAGE (FLA) REFERS TO THE BOILER'S RATED CURRENT DRAW AT HIGH FIRE.

NOTES:

- 1. STEAM OUTPUT LB/HR: FROM 0 PSIG AT 212°F (0 KG/CM² AT 100°C)
- 2. ALL CLEARANCES ARE FACTORY RECOMMENDATIONS. CONSULT LOCAL JURISDICTION FOR EXACT CODE COMPLIANCE.
- 3. FULTON RECOMMENDS MINIMUM CLEARANCE OF 36" IN FRONT OF ELECTRICAL PANELS AND 24" AROUND SIDES OF BOILER.
- 4. PLEASE REFER TO THE O&M MANUAL FOR ADDITIONAL INFORMATION REGARDING CLEARANCES AND INSTALLATION INSTRUCTIONS.
- 5. ALL DIMENSIONS INSIDE () DENOTE REFERENCE DIMENSIONS.
- 6. ALL DIMENSIONS INSIDE □ DENOTE OVERALL DIMENSIONS.
- 7. WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND/OR DIMENSIONS. ALL INFORMATION IS SUBJECT TO CHANGE BASED ON ADDITION OF ANY OPTIONAL EQUIPMENT AND/OR ACCESSORIES. PLEASE CONSULT THE FACTORY FOR PROJECT SPECIFIC ESTIMATES IF ADDITIONAL OPTIONS OR ACCESSORIES ARE REQUIRED.
- 8. SAFETY RELIEF VALVE SIZING IS BASED ON 100 PSIG TRIM. OTHER TRIM PRESSURES WILL CHANGE SAFTEY VALVE SIZE.

RAWING NUMBER 9-FBE-108PDS

Fulton Group N.A., Inc 972 Centerville Road Pulaski, New York USA 13142

SHEET 1 OF 1

-

Fution